

+ Option

- Maintenance Hour Meter TP-22 available ※1



- Rubber Mat (Reversible Design) ※2



NEW

MVC-T90 VAS
(104kg)



NEW

MVC-T100D VAS
(116kg)



[15.0kN]

NEW

MVC-T90
(102kg)



NEW

MVC-T100D
(113kg)



MVC-110DA
(125kg)



MVC Specifications

| model | weight (kg) | dimensions (mm) | plate size (mm) | vibrating frequency Hz (V.P.M.) | centrifugal force (max) kN (kgf) | max.traveling speed (m/min) | max.limited gradeability (%) | power source kW (PS) |
|--|--------------|--|-------------------|---------------------------------|----------------------------------|-----------------------------|------------------------------|---|
| MVC-40GB (Folding Handle) | 46 (47) | H : 920 H1: 590 L : 855 | W: 290 L1: 420 | 103 (6,200) | 7.2 (730) | | | Subaru EH09-2F max.output 2.1 (2.8) |
| MVC-50GB (Folding Handle) <Folding Handle/ water tank> | 59 (60) <67> | H : 920 H1: 545 L : 915 <L: 975> | W: 345 L1: 460 | 97 (5,800) | 9.8 (1,000) | | | Subaru EX13D max.output 3.2 (4.3) Honda GX120 max.output 2.6 (3.5) |
| MVC-F60R MVC-F60H | 74 73 | H : 860 H1: 590 L : 905 | W: 350 L1: 510 | | 10.1 (1,030) | | | |
| MVC-F70R MVC-F70H | 81 | | W: 420 L1: 510 | 93 (5,600) | 12.0 (1,220) | | | Subaru EX17D max.output 4.2 (5.7) Honda GX160 max.output 3.6 (4.9) |
| MVC-F80R MVC-F80H | 87 | H : 860 H1: 570 L : 915 | W: 450 L1: 570 | | 13.7 (1,400) | 25 | 35 | |
| MVC-T90R | 102 | H : 825 H1: 598 L : 1,100 | | | | | | Subaru EY20-3D max.output 3.7 (5.0) |
| MVC-T90H | 101 | H : 825 H1: 560 L : 1,100 | W: 500 L1: 525 | 100 (6,000) | 15.0 (1,530) | | | Honda GX160 max.output 3.6 (4.9) |
| MVC-T100D | 113 | H : 825 H1: 650 L : 1,100 | | | | | | Yanmar L48N max.output 3.5 (4.7) |
| MVC-110DA | 125 | H : 925 H1: 535 L : 1,130 | W: 520 L1: 670 | 97 (5,800) | 21.6 (2,200) | | | Subaru DY27-2D max.output 4.4 (6.0) |