



CDL Wet drill bits

for reinforced concrete | in TGD®-Technology (from Ø 47 mm)

- + **Consistently very fast cutting performance and noticeable smooth running** with TGD® Technology (TYROLIT GRAIN DISTRIBUTION), a unique technology developed by TYROLIT for the optimised distribution of grain.



- + **Very long lifetime.**

Drill motors up to 3 kW | soft to medium-hard concrete aggregates. Quality tools for the most demanding applications and maximum economic

efficiency. Excellent and consistent performance, universal use and smooth core removal. Segment-ed drill from Ø 47 mm with TGD®


Technology and segment height of 11.3 mm. Laser welded segments up to a Ø 300 mm for maximum safety.



CDL Wet drill bits

for reinforced concrete | in TGD®-Technology (from Ø 47 mm)



	Type no.	Dimension	Segment height
	HOHL3		
	497349	12x400xR½"	7
	854317	14x400xR½"	7
	474990	15x400xR½"	7
	474991	16x400xR½"	7
	474993	18x400xR½"	7
	474995	20x400xR½"	7
	474997	22x400xR½"	7
	475000	24x400xR½"	7
	475009	25x400xR½"	7
	475010	28x400xR½"	7
	475011	30x400xR½"	7
	475012	32x400xR½"	7
	500072	35x450xR½"	7
	475014	37x450xR½"	7
	475015	40x450xR½"	7
475016	42x450xR½"	7	